

NEOGI FLOW SCOPE

(ELECTRONIC)



NTR/08 (FOR MOBILE USE) & **NTR/09** (FOR STATIC USE)



FEATURES :

- ❖ ACCURACY: $\pm 0.1\%$ (OUTPUT VOLUME > 99.9% OF INPUT VOLUME) .
- ❖ POSITIVE DISPLACEMENT METER .
- ❖ REPEATABILITY 100% .
- ❖ FLOW RATE : 5 TO 60 LPM .
- ❖ ELECTRONIC REGISTER UNIT WITH 6 DIGIT LCD DISPLAY .
- ❖ THERE IS AN INBUILT PRINTER BY WHICH ONE CAN PRINT THE BILL AFTER EACH DELIVERY .
- ❖ THE RATE OF THE FUEL CAN BE SET VERY EASILY WITH THE HELP OF THE KEYPAD .
- ❖ THE CLOCK CAN BE SET IN 24H FORMAT WITH THE HELP OF THE KEYPAD .
- ❖ THE COMPANY NAME , ADDRESS , CONTACT NUMBER, EMPLOYEE ID, NOZZLE ID ,FUEL TYPE , DENSITY OF THE FUEL CAN BE SET WITH HELP OF KEY PAD WHICH CAN BE PRINTED ON THE BILL .
- ❖ MEASURES, MONITORS THE EXACT VOLUME OF LIQUID SPECIALLY PETROLEUM PRODUCTS LIKE LDO , HSD , KEROSENE ,FURNACE OIL , BIO DIESEL ETC. FUNCTIONS EQUALLY IN STATIC OR MOBILE CONDITIONS IN URBAN , SUBURBAN & RURAL AREAS .

PROMPT MAINTENANCE SUPPORT

CERTIFICATION : LEGAL METROLOGY GOVT. OF INDIA





LOCATION OF NEOGI FLOW SCOPE (NTR/08) ON TRUCK :

